52" Basics Pro Select Fan Matte White

330017MWH (Matte White)

Project Name:
Location:
Type:
Qty:
Comments:



Airflow		
CFM (High)	4200	
CFM (Low)	1523	
RPM (High)	161	
RPM (Low)	57	

Certifications/Qualifications

Location Rating	CSA UL Listed Dry
	www.kichler.com/warranty

Dimensions

Base Backplate	5.25 DIA
Downrod 1	1.00 OD X 4.00"
Downrod 2 - Measurement A	14.50"
Downrod 2 - Measurement B	7.50"
Downrod 2 - Measurement C	11.50"
Weight	19.71 LBS
Height	17.50"
Width	52.00"

Electrical

Amps (High)	0.43
Amps (Low)	0.07
Motor Size	153MM X 15MM
Motor Type	AC

Mounting/Installation

Minimum Distance from Far Floor	nto 7feet
Interior/Exterior	Interior
Lead Wire Length	78
Low Ceiling Adaptable	Yes, Dual Mount Included
Mounting Weight	15.09 LBS

Photometrics

Color Rendering Index	80
Kelvin Temperature	2700K

Primary Lamping

Downward-facing Bulbs	3 X 4
Downlight Included	Yes
Downlight Option	Removable
Watts (High)	52
Watts (Low)	9

Product/Ordering Information

SKU	330017MWH
Finish	White
Style	Traditional
UPC	783927572392

Specifications

Blade Finish 1	MATTE WHITE
Blade Finish 2	SILVER
Blade Material	WOOD
Blade Pitch	12
Blades Included	Yes
Blade Sweep	52
Diffuser Description	White Etched
Material	STEEL

Max Ster	n Tilt	22 Degrees
Number	of Blades	5
Blades R	eversible	Yes
Additio	onal Finishes	
	Brushed Nickel	
	Matte White	
	Satin Black	
	Satin Natural Bro	onze
	White	

Kichler 7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010 Toll free: 866.558.5706 or kichler.com

Notes:

Notes:

1) Information provided is subject to change without notice.
All values are design or typical values when measured under laboratory conditions.

2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.



Geno LED 54" Fan Brushed Stainless Steel

330001BSS (Brushed Stainless Steel)

Project Name:	
Location:	
Type:	
Qty:	
Comments:	



Airflow		
CFM (High)	5147	
CFM (Low)	1774	
RPM (High)	157	
RPM (Low)	58	

Certifications/	Oualifications

Location Rating	CSA UL Listed Dry
Title 20 Compliant	Yes
	www.kichler.com/warranty

Dimensions

Base Backplate	5.25 DIA
Downrod 1	1.00 OD X 4.50"
Weight	24.50 LBS
Height	14.50"
Width	54.00"

Electrical

Amps (High)	0.67	
Amps (Low)	0.28	
Motor Size	188MM X 25MM	
Motor Type	AC	

Mounting/Installation

Minimum Distance from Fan t Floor	o 7feet
Interior/Exterior	Interior
Lead Wire Length	78
Mounting Weight	24.50 LBS

Photometrics

Color Rendering Index	80
Color Temperature Range	3000
Kelvin Temperature	3000K

Primary Lamping

Downward-facing Bulbs	1 X 17W
Dimmable	Yes
Dimmable Notes	Recommended for use with Kichler Fan Controls
Downlight Included	Yes
Downlight Option	Integrated
Watts (High)	80
Watts (Low)	14

Product/Ordering Information

SKU	330001BSS
Finish	Stainless Steel
Style	Transitional
UPC	783927521116

Specifications

Blade Finish 1	SILVER
Blade Finish 2	WALNUT
Blade Material	WOOD
Blade Pitch	14
Blades Included	Yes
Blade Sweep	54
Diffuser Description	Etched Cased Opal
Material	STEEL

Max Stem Tilt	18 Degrees
Number of Blades	5
Remote Included	Yes
Blades Reversible	Yes

Additional Finishes

4		h
4		,

Brushed Stainless Steel



Matte White



Olde Bronze



Satin Black

Kichler

7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010 Toll free: 866.558.5706 or kichler.com

Notes:

All values are design or typical values when measured under laboratory conditions.

2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.



Clermont LED 52" Fan Satin Natural Bronze

35156 (Satin Natural Bronze)

Project Name:	
Location:	
Type:	
Qty:	
Comments:	

Certifications/Qualifications

Title 20 Compliant	Yes www.kichler.com/warrantu
	www.kichier.com/ warrantg
Dimensions	
Height	18.50"
Length	52.00"

Mounting/Installation

Low Ceiling Adaptable

Product/Ordering Information

SKU	35156.00
Finish	Bronze
Style	Industrial
UPC	737995351564

Additional Finishes



Satin Natural Bronze



7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010 Toll free: 866.558.5706 or kichler.com

Notes:

1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.

2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference



Sutter Place Select LED 2700K 52" Fan Antique Pewter

339501AP (Antique Pewter)

Project Name:	
Location:	
Type:	
Qty:	
Comments:	



Airflow		
CFM (High)	3832	
CFM (Low)	1598	
RPM (High)	152	
RPM (Low)	70	

Certifications/Qualifications

Location Rating	CSA UL Listed Dry
	www.kichler.com/warranty

Dimensions

Base Backplate	5.25 DIA
Downrod 1	1.00 OD X 4.00"
Downrod 2 - Measurement A	15.25"
Downrod 2 - Measurement B	8.00"
Downrod 2 - Measurement C	12.00"
Downrod 2	FLUSH MOUNT"
Weight	18.61 LBS
Height	18.00"
Width	52.00"

Electrical

Amps (High)	0.42
Amps (Low)	0.23
Motor Size	152 MM X 15 MM
Motor Type	AC INDUCTION

Mounting/Installation

Minimum Distance from Fan to 7feet Floor	
Interior/Exterior	Interior
Lead Wire Length	78
Low Ceiling Adaptable	Yes, Dual Mount Included
Mounting Weight	18.61 LBS

Photometrics

Color Rendering Index	80
Kelvin Temperature	2700K

Primary Lamping

Downlight Included	Yes
Downlight Option	Removable
Lamp Included	Included
Lamp Type	E12
Light Source	LED
# of Bulbs/LED Modules	3
Socket Type	CAND
Watts (High)	49
Watts (Low)	11

Product/Ordering Information

SKU	339501AP
Finish	Pewter
Style	Traditional
UPC	783927600361

Specifications

Blade Finish 1	LIGHT CHERRY
Blade Finish 2	BLACK CHERRY
Blade Material	WOOD

Blade Pitch	12
Blades Included	Yes
Blade Sweep	52
Diffuser Description	Satin Etched
Material	STEEL, PLYWOOD, GLASS
Max Stem Tilt	22 Degrees
Number of Blades	5
Blades Reversible	Yes

Additional Finishes



Antique Pewter



Matte White



Oil Brushed Bronze



Olde Bronze

Kichler 7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010 Toll free: 866.558.5706 or kichler.com

Notes:
1) Information provided is subject to change without notice.
All values are design or typical values when measured under laboratory conditions.
2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

